

MCI Series

CHARACTERISTICS

- Monolithic inorganic material construction.
- Closed magnetic circuit avoids crosstalk.
-
-

Compliant with RoHS legislation and also support

Quantity: 4000pcs

APPLICATION

-



MCI1608-22NJ	22	±5%	16	12	300	0.40	1600	100
MCI1608-27NJ	27	±5%	16	12	300	0.45	1400	100
MCI1608-33NJ	33	±5%	17	12	300	0.55	1200	100
MCI1608-39NJ	39	±5%	18	12	300	0.60	1100	100
MCI1608-47NJ	47	±5%	17	12	300	0.70	900	100
MCI1608-56NJ	56	±5%	17	12	300	0.75	900	100
MCI1608-68NJ	68	±5%	18	12	300	0.85	700	100
MCI1608-82NJ	82	±5%	18	12	300	0.95	600	100
MCI1608-R10J	100	±5%	18	12	300	1.00	600	100
MCI1608-R12J	120	±5%	16	8	300	1.20	500	50
MCI1608-R15J	150	±5%	13	8	300	1.20	500	50
MCI1608-R18J	180	±5%	13	8	300	1.30	400	50
MCI1608-R22J	220	±5%	12	8	300	1.50	400	50
MCI1608-R27J	270	±5%	14	8	150	1.90	300	50

Operating Temperature : -40 ~ +85 °C

Temperature rise current: the actual value of DC current when the temperature rise is $\Delta T 30^{\circ}\text{C}$

